

USES & APPLICATIONS

For use with any Bushman water tank. This kit may be used to connect your tank to an external pump or to connect multiple tanks together.

CONTENTS OF KIT

(1) 1" I.D. Flex Hose - 4'
(2) 1" Male Adapter
(2) 90 Deg. Elbow
(1) 1" Ball Valve
Teflon Thread Tape
Installation Instructions

TOOLS REQUIRED

Crescent Wrenches and/or Open-End Wrenches.

Congratulations on your selection of a Bushman Flex Hose Kit.

Bushman is known around the world for its quality products. Your Flex Hose Kit has been designed and manufactured to give you long, trouble-free service. For proper use it is important to carefully read through these instructions and to fully observe the given advice.



*If you have any concerns or questions, please call us at:
1-866-920-TANK (1-866-920-8265)*

Monday through Friday, 8:00am - 5:00pm PST

FLEX HOSE KIT | INSTALLATION INSTRUCTIONS

1. Remove the plug from the discharge location on your tank.



2. Using teflon tape, install the Ball Valve into the tank.



FLEX HOSE KIT | INSTALLATION INSTRUCTIONS

3. Using teflon tape, attach the Adapter to the Ball Valve.



4. Ensure there are no kinks in the hose and then attach the hose to the adapter using the included grease to ease assembly then tighten the collar.



5. Finished Assembly



6. Photo below shows the connection of the two tanks using the two elbows supplied with kit.



MAINTENANCE

The Flex Hose Kit needs no regular maintenance.